

Broadband Router Model No.: VRT501



The Visonicom VRT501 is the most compact multifunctional broadband SOHO router with built-in firewall to prevent the LAN from attack outside, supports virtual server, DMZ, UPnP, NIC MAC and IP bundling, Domain filtering and static router, free firmware upgrade, 4-port 10/100M switches integrated.

Features:

- * 1*10M/100M auto negotiation WAN port, connectible to xDSL/Cable Modem or Ethernet
- * 4*10M/100M auto negotiation LAN ports with 4 10M/100M switches integrated
- * Compliant with IEEE802.3 Ethernet Standard and IEEE802.3u Fast Ethernet Standard
- * Full duplex IEEE802.3x flow control, Half duplex Backpressure flow control
- * TCP/IP, PPPoE, DHCP, ICMP, NAT, SNTP supported
- * UPnP supported
- * VPN pass through supported
- * Built-in DHCP sever
- * Virtual server and DMZ supported
- * Built-in static router
- * Prevent D.O.S network attack
- * Supports MAC address filter, Internet access controllable
- * Supports URL filter, Internet access controllable
- * Local, Remote Web management, online firmware upgradeable

Specifications:

| | |
|---------------------|---|
| Standard/Protocols | IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.1X, TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP |
| Ports | 4 10/100M auto detect RJ45 ports(Auto MDI/MDIX) |
| | 1 ↑ 10/100M Base-T WAN port(Auto MDI/MDIX) |
| Transmission Media | 10Base-T:Cat 3 or above UTP |
| | 100Base-TX:Cat 5 UTP |
| LED Indicator | Power, SYS, WAN link/act LAN link/act |
| Working Environment | Working temperature:0°C~45°C; |
| | Store temperature:-20°C~70°C |
| | Working humidity :10%~85% RH Non-condensing; |

| | |
|------------------------|--|
| | Storage Temperature:5%~90% RH Non-condensing |
| Power Supply | Power adaptor output: AC9V, 0.6A |
| Max Power Consumption: | 3W |